

SENSIT DISPLAY

| 3-digit led display for parking guidance



KEY FEATURES:

- LED display for outdoor use, single sided
- Automatic regulated luminance
- TCP/IP connection to SENSIT REST Interface
- Easy configuration in SENSIT Interface Software
- Power over Ethernet (PoE+)
- Stand-alone parking guidance

SENSIT Display

The SENSIT Display enables the visualisation of available parking spaces for stand-alone parking guidance installations. The display is designed for outdoor use, indicating the number of available parking spaces per parking lot making it easy to guide motorists to an available parking space.

Availability of parking spaces can be indicated per zone for the specific zone the SENSIT Display is allocated to. Configuration of the display can be realized using the SENSIT Interface Software.

Surrounding conditions

The display has adequate mechanical protection to withstand demanding environmental conditions and automatic regulation of LED luminance to optimally adapt to surrounding conditions.

Power and connectivity

The SENSIT Display is powered by mains or Power over Ethernet (PoE+). For connectivity to the SENSIT Interface Software, TCP/IP Ethernet is used.

SENSIT Display Option

Advanced configuration settings of the SENSIT Display can be adjusted with the SENSIT Display Option; a separate software feature within the SENSIT Interface Software. The following features are available:

- Display name: set and adjust the names of several SENSIT Displays for an organized overview of the displays within the SIS' map monitor.
- Threshold: set and adjust threshold levels for the displayed number of available parking spaces.
- Reservation: reserve a specific amount of parking spaces for events, visitors or vips.
- Zones: combine multiple parking zones/ parking lots to be displayed on one SENSIT Display.
- Activation schedules: configure the time and days per week on which the SENSIT Display must be active.
- Relays settings: easily control the output of the 3 relays within the SENSIT Display. For example, trigger a red light or block a barrier from opening when the parking zone is fully occupied.

SPECIFICATIONS

Technical information	SENSIT Display
Power	Power cable (1,5m standard included) 110~230 VAC / 25 Watt, PoE+
Connectivity	Ethernet cable of 1,5 meter length (standard included)
Enclosure material	Stainless steel casing RVS 316
Operating temperature	-20°C tot +60°C temperature range
Protection	IP65, UV protected, ANSI/UL94 Flammability Classification (UL94--USA standard)
Humidity	Up to 90%, non-condensing
Luminance regulation	Auto adjustment
Relay output	Low power relay output available, max. 3 relays
Color	Amber
Character height (h x w)	160 x 100mm [6.3 x 3.9 inch]
Intensity	5.000 cd/m2, readable in full sunlight
Viewing angle	70°/35°
LED Pitch	10 mm
Overall dimensions	330 x 221 x 171 mm (13 x 8,7 x 6,7 inch)
Display dimensions	320 x 160 x 15 mm (12,6 x 6,3 x 0,6 inch)
Mounting	4 threaded holes M5 (bolts included)
Weight	5,9 kg (208 oz)
Part number	9221557 SENSIT Display 8027153 SENSIT Display Option
Document version nr.	v1.1